



Product Data Sheet

BLAZE RACING MULTI-GRADE SAE 20W-50

DESCRIPTION

BLAZE RACING MULTI-GRADE SAE 20W-50 with TS³ is a high-quality engine oil designed to meet the performance requirements of a wide range of gasoline engines operated under vehicle manufacturer's recommended maintenance procedures.

The unique additive technology called Thermal Stress Stabilizing System (TS3) keeps the oil stable even at extreme temperatures, providing ultimate protection from engine stress.

PROPERTIES

- Provides better wear protection
- Keeps engine clean through superior control of sludge and deposits
- Promotes extended oil drain characteristics

GRADE

- SAE 20W-50

TYPICAL CHARACTERISTICS*

Color, ASTM	L1.5
Density at 15°C, kg/L	0.8731
Flash Point, COC, °C	250
Kinematic Viscosity at 40°C, cSt	168.6
Kinematic Viscosity at 100°C, cSt	19.30
Viscosity Index	131
TBN, mg KOH/g	4.6

**Only typical results and may vary per production blend*

APPLICATION

- Gasoline-powered vehicles

QUALITY LEVELS

- It has the performance profile of:
 - API SL/CF

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.