



PETROGREASE MP

DESCRIPTION

PETROGREASE MP is a good quality lithium-type multi-purpose grease for plain and anti-friction bearings found in a wide variety of automotive, farm, industrial and construction equipment.

PROPERTIES

- Provides excellent water resistance and thermal stability under normal conditions
- Resists formation of deposits caused by high operating temperatures
- Adheres well to lubricated parts, sealing them from dirt and abrasive materials
- Maintains consistency during prolonged storage

GRADE

- NLGI Nos. 2 and 3

APPLICATIONS

- Automotive chassis and wheel bearings, plain and anti-friction bearings found in a wide variety of automotive, farm, industrial and construction equipment
- Operating temperature up to 120°C

TYPE

- Lithium soap multi-purpose grease

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS

	MP 2	MP 3
Appearance, Texture	Smooth, Uniform and Tacky	Smooth, Uniform and Tacky
Color, Visual	Yellow	Yellow
Scent	Lemon	Lemon
Worked Penetration at 25°C, 100g, 5 secs, mm/10 60 strokes	270	231
Dropping Point, °C	206	204
Tilted Wheel Bearing Test		
Slump Rating	Passes	Passes
Leakage in grams	Nil	Nil
Base Oil Viscosity, cSt at 40°C	91.65	89.95