



PETRON ATF PREMIUM HTP

DESCRIPTION

Petron ATF Premium HTP is a fully synthetic, premium grade, high performance automatic transmission fluid formulated to provide excellent resistance to oxidation even under high temperature and severe operating condition.

PROPERTIES

- Provides excellent resistance to oxidation from exposure to high temperature
- Provides extended protection in friction stability and clutch durability
- Protects gears, bearings, clutch plates, seals, and other components from wear and corrosion
- Excellent foaming characteristics for optimum operability and longer transmission life

GRADE

SAE 20

APPLICATION

- Suitable for use in most light duty planetary gear service fill applications
- Suitable for use for
 - General Motor's Dexron IIIH
 - Mercon V, Honda Z-1, Hyundai/Kia Red 1-K, SP-II, SP-III
 - Isuzu ATF II, III
 - Mazda F-1, M-III, Type T-IV
 - Mitsubishi SP-II, SP-III
 - Nissan Matic D, J, K, W
 - Subaru HP
 - Suzuki 3314, 3317
 - Toyota / Lexus D-II, T, T-III, T-IV
 - Allison C-4
 - ATF Specifications from the following OEMs: Audi, BMW, Chrysler, Daimler, Dodge, Jaguar, Jeep, Land Rover, MAN, Maserati, Mercedes-Benz, Mini, Porsche, Volkswagen, and Volvo

QUALITY LEVELS

- It has the performance profile of:
 - JASO IA

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS*

Density at 15°C, kg/L	0.8505
Flash Point, COC, °C	218
Color, ASTM	Red
Kinematic Viscosity at 40°C, cSt	35.72
Kinematic Viscosity at 100°C, cSt	6.743
Viscosity Index	149
TBN, mgKOH/g	3.6

* Only typical properties and may vary per production batch.