



Product Data Sheet

RIDER 4T PREMIUM MULTIGRADE SAE 20W- 50

DESCRIPTION

PETRON RIDER 4T PREMIUM MULTIGRADE SAE 20W-50 motorcycle engine oil is formulated for four-stroke motorcycle equipped with either wet or dry clutch systems for maximum engine protection and reliable transmission performance under severe conditions like temperature, high speed operation and challenging terrain.

It contains TCS or Thermal Control System to enhance the oil's thermal stability, volatility profile and oxidation stability

PROPERTIES

- Excellent stability to resist oil thinning and breakdown under extreme operating conditions
- Reliable clutch friction for good clutch engagement and operation for wet clutch systems
- Superior wear protection on engine parts for longer engine life

GRADE

- SAE 20W-50

APPLICATIONS

- Four-stroke motorcycle engines

QUALITY LEVEL

- It has the performance profile of:
 - API SL
 - JASO MA/MA2

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS

Density at 15°C, kg/L	0.8696
Flash Point, COC, °C	244
Color, ASTM	2.0
Kinematic Viscosity at 40°C, cSt	157.7
Kinematic Viscosity at 100°C, cSt	18.10
Viscosity Index	128
Pour Point, °C	-26
TBN, mgKOH/g	6.6