



PETRON REV-X FULLY-SYNTHETIC SAE 5W-40

DESCRIPTION

REV-X FULLY-SYNTHETIC SAE 5W-40 with DC Tech is a top tier product specially formulated for heavy duty diesel engines to provide excellent protection under extreme driving conditions.

PROPERTIES

- It prevents soot and piston deposits to maintain superior engine cleanliness and efficiency.
- It gives excellent protection against wear and corrosion for longer engine life.
- It provides exceptional engine protection with outstanding oxidation resistance.
- It is suitable for vehicles with emissions control systems such as diesel particulate filters (DPF) and exhaust gas recirculation (EGR).

GRADE

SAE 5W-40

APPLICATION

- Turbocharged or supercharged high performance heavy duty diesel engines operating under both low speed-high load and high speed-high load conditions

QUALITY LEVELS

- It is approved and certified according to the specifications of the following:
 - API CJ-4/SM
 - Cummins CES 20081
 - MB - Approval 228.31
- It has the performance profile of:
 - ACEA E9
 - Caterpillar ECF-2/ECF-3

AVAILABLE PACKAGES

**Please contact our Sales Team for the available packages*

TYPICAL CHARACTERISTICS

Color, ASTM	L 3.0
Specific Gravity at 15.6 °C	0.8545
Kinematic Viscosity at 40°C, cSt	88.40
Kinematic Viscosity at 100°C, cSt	14.35
Viscosity Index	169
Flash Point, COC, °C	200
TBN, mg KOH/g	10.4