



REV-X MULTIGRADE SAE 15W-40

DESCRIPTION

REV-X MULTIGRADE SAE 15W-40 is high-quality engine oil designed for indirect injected diesel engines including off-road vehicles. It can be used for naturally aspirated, turbo-charged and supercharged diesel engines. It is suitable for mixed fleets of diesel and gasoline-powered vehicles such as trucks and buses.

PROPERTIES

- Effective control of piston deposits
- High-level protection from wear and copper-based corrosion for longer engine life
- High resistance against oil-thickening and gum-formation

GRADE

- SAE 15W-40

APPLICATIONS

- Mixed fleets of automotive diesel and gasoline-powered vehicles such as trucks and buses.
- Can also be used for off-road vehicles, agricultural tractors and equipment

QUALITY LEVELS

- It has the performance profile of:
 - API Service CF/SF
 - Mercedes Benz p227.1
 - ACEA E1

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS

Specific Gravity at 15°C	0.8795
Flash Point, COC, °C	226
Kinematic Viscosity at 40°C, cSt	103.2
Kinematic Viscosity at 100°C, cSt	14.06
Viscosity Index	138
TBN, mg KOH/g	7.5