



## Product Data Sheet

# PETRON GASUL

### DESCRIPTION

Petron LPG is a clean burning liquefied petroleum gas (LPG) consisting of a mixture of propane and butane. It is used as fuel for cooking, lighting, and industrial applications.

### APPLICATION

- Fuel for ovens, furnaces, gas stoves, gas lamps, pilot flame in boilers, cutting, soldering, and brazing operations in metal fabrication.

### TYPE/QUALITY LEVEL

- Liquefied Petroleum Gas (LPG)

### AVAILABLE PACKAGES

- Bulk
- Cylinders

### TYPICAL CHARACTERISTICS

Density at 15°C, kg/l	0.5555
Copper Corrosion, 1hr. at 37.8°C	1
Free Entrained Water, % vol.	Nil
Odorant, g/Kl	45
Oil Stani 'O' Number	0
Oily Residue at 105°C, mg/100ml	0.3
Residue at 37.8°C, % vol.	0
C3 Hydrocarbon, % vol.	37.2
C4 Hydrocarbon, % vol.	62.5
C5 Hydrocarbon, % vol.	0.3
Sulfur, mg/kg	45
RVP of LPG at 37.8°C, kPa	680
Weathering at 2.2°C, % vol.	99
Diene as 1-3 butadiene, %wt.	0