



## Product Data Sheet

# RIDER 4T MULTIGRADE SAE 20W-40

### DESCRIPTION

**PETRON RIDER 4T MULTIGRADE SAE 20W-40** is a high-quality motorcycle oil most suited for four-stroke motorcycles equipped with either wet or dry clutch systems. It provides engines with reliable protection and effective cleaning action for dependable performance under continuous and heavy-duty driving conditions.

It contains TCS or Thermal Control System to enhance the oil's thermal stability, volatility profile and oxidation stability.

### PROPERTIES

- Contains anti-wear additive system to form a protective layer on engine parts to prevent engine wear
- Superior ability to withstand heat for longer engine protection resulting to lower maintenance cost
- Superior wear protection on engine parts for longer engine life

### GRADE

- SAE 20W-40

### APPLICATIONS

- Four-stroke motorcycle engines

### QUALITY LEVEL

- It has the performance profile of:
  - API SJ
  - JASO MA/MA2

### AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

### TYPICAL CHARACTERISTICS

Density at 15°C, kg/L	0.8699
Flash Point, COC, °C	224
Color, ASTM	2.0
Kinematic Viscosity at 40°C, cSt	97.63
Kinematic Viscosity at 100°C, cSt	13.57
Viscosity Index	140
Pour Point, °C	-31
TBN, mgKOH/g	4.5