



## Product Data Sheet

# RIDER 4T SYNTHETIC BLEND SAE 15W-50

### DESCRIPTION

**PETRON RIDER 4T SYNTHETIC BLEND SAE 15W-50** is formulated with unique additive technology designed to provide superior performance in four-stroke motorcycle applications.

It contains TCS or Thermal Control System to enhance the oil's thermal stability, volatility profile and oxidation stability

### PROPERTIES

- Excellent clutch friction performance durability
- Superior protection against engine wear and gear pitting
- Excellent engine cleanliness, TBN retention and resistance to thermal stress

### GRADE

- SAE 15W-50

### APPLICATIONS

- Air-cooled and liquid-cooled four-stroke motorcycle engines

### QUALITY LEVEL

- It has the performance profile of:
  - API SN
  - JASO MA/MA2

### AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

### TYPICAL CHARACTERISTICS

Color, ASTM	1.5
Density at 15°C, kg/L	0.8732
Kinematic Viscosity at 40°C, cSt	143.2
Kinematic Viscosity at 100°C, cSt	18.26
Viscosity Index	143
Flash Point, COC, °C	228
Pour Point, °C	-36
TBN, mg KOH/g	7.2