



Product Data Sheet

BLAZE RACING SYNTHETIC BLEND 5W-30

DESCRIPTION

BLAZE RACING SYNTHETIC BLEND 5W-30 with TS³ is a multi-grade synthetic blend engine oil designed to give maximum engine protection, improved oxidation stability, and better wear protection.

The unique additive technology called Thermal Stress Stabilizing System (TS³) keeps the oil stable even at extreme temperatures, providing ultimate protection from engine stress.

PROPERTIES

- Has excellent thermal stability and oxidation resistance for longer oil drain interval
- Provides better volatility and viscosity retention properties
- Provides excellent chain wear protection and improves piston cleanliness and fuel economy
- Provides protection against low-speed pre-ignition (LSPI) in turbocharged gasoline direct injection engines

GRADE

- SAE 5W-30

APPLICATION

- Gasoline-powered cars, sports utility vehicles, vans, and light-duty trucks

QUALITY LEVEL

- It has the performance profile of:
 - API SP

AVAILABLE PACKAGE

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS

Density at 15°C, kg/L	0.8507
Flash Point, COC, °C	228
Color, ASTM	L2.5
Kinematic Viscosity at 40°C, cSt	56.61
Kinematic Viscosity at 100°C, cSt	9.764
Viscosity Index	159
TBN, mg KOH/g	6.5